




KEY FEATURES

- DECK:**
 30,000-lb structural deck capacity, available in many different configurations to meet your hauling needs to transport.
- WINCH:**
 20,000-lb Worm or Planetary Winch options with air free spool.
- REAR TOW:**
 Options from rear dock stabilizer with extendable pintle hitch or wheel lift with hitch.

SPECIFICATIONS

CARRIER DECK	
Capacity	30,000-lb
Deck Width	96-in, 102-in
Deck Length	24-ft, 26-ft, 28-ft, 30-ft
Material Type	Apitong Wood, Steel Diamond Over Wood, Traction Plate Decking Over Wood
WHEEL LIFT	
Lift Capacity	5,000-lb
Tow Capacity	12,000-lb
Maximum Extended Reach from End of Bed	56.2-in
WINCH	
Winch Capacity	20,000-lb
CHASSIS	
Minimum GVWR	46,000-lb
Usable Clear Space Cab-to-Tandem, CT (Deck Length)	134-in - 146-in (24-ft) 158-in - 170-in (26-ft) 182-in - 196-in (28-ft) 206-in - 220-in (30-ft)



Visit jerrdan.com for more info on warranty.

FEATURES	STANDARD	OPTIONAL
CONTROLS		
Dual Lighted Side Controls	•	
Wireless Remote (Up to 5 Functions)		•
DECK & SUBFRAME		
Fixed, Deluxe or Stationary Headboard		•
Hydraulic Tank w/ Filter	•	
Hydraulic Pressure Gauge Driver Side Control Station	•	
Outboard Tilt Cylinders	•	
Hose & Wiring Track System	•	
6 Keyslots: 2 Front, 4 Rear	•	
Outside Stake Pockets w/ Rubrail & Pipe Spools		•
Fork Lift Stop		•
Winch Cage		•
Hi Vis Reflective Tape Rear of Sub Frame		•
3 Step Folding Ladder (Driver, Passanger, or Both)		•
12 Pair Inside Outside Key Slot Strips		•
11 Pair Outside Key Slot Strips		•
Yellow Anti-Slip on Rear Tail Section		•
Yellow Anti-Slip on Rubrails		•
Propane Tank Holders		•
Chain Racks on Headboard		•
5-in High Removable Rub Rails		•
LIGHTING & ELECTRICAL		
LED Lighting	•	
Rear Awareness Indicator Lights (RAIL)		•
LED Work Lights (Upper headboard, lower at winch, rear lower subframe)		•
Backup Camera System		•

FEATURES	STANDARD	OPTIONAL
TOWING ACCESSORIES		
5,000-lb Wheel Lift		•
Hydraulic Rear Dock Stabilizer (Various Trailer Towing Provisions Available)		•
Pintle Hitch- Manual Extension		•
Pintle Hitch- Hydraulic Extension		•
8 Point Tie Down Kit		•
Pivot Joints (Cylinders and Pivot Pins)		•
ACCESSORIES		
Air Supply Disconnect (End of Subframe Mounted at LH Taillights)		•
Stainless Steel Quarter Fenders		•
Toolbox (36-in, 48-in or 60-in)		•
Toolbox Trays		•
Traffic Cone Storage		•
WINCH & WIRE ROPE		
20,000-lb Worm Gear Winch w/ 5/8-in x 75-ft EIPS Galvanized Wire Rope, Air Free Spool	•	
Winch Tensioner Plate: 20,000-lb		•
Winch Roller Guide: 20,000-lb		•
20,000-lb Planetary Winch w/ 5/8-in x 75-ft EIPS Galvanized Wire Rope, Air Free Spool		•