




KEY FEATURES

- BOOM:**
 24,000-lb retracted capacity 2-stage wrecker boom.
- UNDERLIFT:**
 6,000-lb lift capacity with frame forks.
- BODY:**
 Modular aluminum construction, designed to provide years of service and ease of maintenance.
- WINCHES:**
 Dual 10,000-lb or 12,000-lb worm gear winches.

RECOVERY BOOM: 2-STAGE	
Retracted Capacity @ 30°	24,000-lb
Extended Capacity @ 30°	8,000-lb
Maximum Hook Height	121-in
Maximum Boom Angle	32°
REACH PAST TAILBOARD	
Reach Past Tailboard - Extended @ 0°	84-in
Reach Past Tailboard - Extended @30°	60-in
UNDERLIFT BOOM	
Retracted Rating L-Arms/Forks	5,000-lb / 6,000-lb
Retracted Reach L-Arms/Forks	59-in / 51-in
Extended Rating L-Arms/Forks	5,000-lb / 6,000-lb
Extended Reach L-Arms/Forks	87-in / 78-in
Positive Tilt	20°
Negative Tilt	20°
Tow Capacity	12,000-lb
WINCHES	
Winch Capacity	10,000-lb / 12,000-lb
Winch Options	Dual
Wire Rope (EIPS Galvanized)	7/16-in x 101-ft (w/Swivel Hook, for 10K Winch) 7/16-in x 150-ft (w/Swivel Hook, for 12K Winch)
CHASSIS	
Minimum GVW Rating	18,000-lb
Minimum Cab-to-Axle, 24-in Tunnel, CA	84-in
Minimum Cab-to-Axle, 24-in Double Tunnel, CA	108-in



Visit jerrdan.com for more info on warranty.



FEATURES	STANDARD	OPTIONAL
CONTROLS		
Dual Side EH Controls with Control Covers	•	
Wired Underlift Remote Control		•
Wireless Underlift Remote Control*		•
Wireless Full-Function Remote Control*		•
BODY		
Lighted Toolboxes	•	
Polished Stainless Rails		•
Aluminum Deck Dress Up Kits*		•
Inner Wheel Well Liners	•	
Black Anti-Skid Top Deck Surface	•	
24-in Aluminum Tunnel Box	•	
Additional 24-in Aluminum Tunnel Box		•
LIGHTING & ELECTRICAL		
DOT Lighting	•	
Backup Alarm	•	
Fold Down Light Bar Mount		•
In-Cab Switch Panel		•
LED Lower Hook-Up Lights	•	
LED Work Lights Upper - Pylon Mounted		•
Backup Camera Kit		•
Steel Tubular Light Pylon	•	
7-Way RV/4-Way Flat Trailer Connection	•	
Aux Air & Gladhands		•

FEATURES	STANDARD	OPTIONAL
BOOM & WINCHES		
No-Lube™ Technology	•	
Greaseable Joints w/ Grease Fittings		•
12T Boom w/Dual Lift Cylinders	•	
Underlift Level Stop Assist System	•	
Winch Rope Tensioner Plate	•	
Remote Freespool Handles	•	
Dual 10,000-lb Worm Gear Winch	•	
Dual 12,000-lb Worm Gear Winch		•
Spade Leg and Wrecker Boom D-Rings (3 Total)	•	
Tailboard D-rings		•
<i>*Available through parts only</i>		