


SPREADER BAR 42K/112L



The Jerr-Dan Spreader Bar is rated at a 42,000 lb capacity when using a 60 degree sling angle and 2 vertical drop lines, at 112" spread. It is designed for use in vertical lifting applications, as well as quick setup and convenient storage. The sling angle chart is attached on the spreader bar for a quick reference of sling angles, and lift capacity.


FEATURES Easy assembly and disassembly for quick setup and convenient storage Integrated angle indicator to determine maximum lifting capacity **SPECIFICATIONS** Weight Assembled 105 lbs. Length Assembled 112 in. Rated Capacity at 60° Sling Angle 42,000 lbs.



JERR-DAN CORPORATION 13224 FOUNTAIN HEAD PLAZA HAGERSTOWN, MD 21742 CAPACITY CHART 717-897-7111			
ASME BTH-1 DESIGN CATEGORY: B SERVICE CLASS: 0 APPROX. ASSEMBLED WEIGHT OF SPREADER BAR: 105 LBS		CAPACITY (LBS) WITH VERTICAL BOTTOM SLINGS	
	30-40	20,000	
	41-50	30,000	
	51-60	42,000	
DO NOT EXCEED RATINGS READ MANUAL BEFORE USIN NSPECT EQUIPMENT BEFOR		100/313130	



Ø JERRDAN.COM






SPREADER BAR 42K/112L

An Oshkosh Corporation Business







SPREADER BAR 42K/112L			
PRODUCT	JD PART NUMBER	DESCRIPTION	
Spreader Bar 42K/112L	1001309755	Spreader Bar Kit	
Storage Bracket Kit – JD50/60 HDR	1001319307	Storage Brackets and hardware for mounting on JD50/60 HDR1000	
Spreader Bar Rigging Kit- Shackles & Round Slings	1001295192	1 – 30t Alloy Shackle 2 – 17t Shackles 2 – 12t Shackles 2 – 8' Orange Round Slings 2 – 12' Blue Round Slings	