



### KEY FEATURES

- DECK:**  
 Built to be tough and reliable with steel construction. 20,000-lb structural capacity.
- WINCH:**  
 Up to 12,000-lb capacity winch for maximum pulling power.
- WHEEL LIFT:**  
 Low profile and versatile. 3,500-lb or 5,000-lb lift capacities.

### SPECIFICATIONS

CARRIER DECK	
Capacity	20,000-lb
Deck Width	102-in
Deck Length	22-ft, 24-ft, 26-ft, 28-ft, 30-ft
Material Type	Steel
WHEEL LIFT- 5,000-LB	
Lift Capacity	5,000-lb
Tow Capacity	12,000-lb
Maximum Extended Reach from Tail to Bed	67-in
WINCH	
Winch Capacity	Single 10,000-lb or 12,000-lb Dual 8,000-lb
10K or 12K Single Winch only	22-ft, 24-ft, 26-ft Deck Only
10K or 12K Single Dual 8K Winches	28-ft Deck Only
Dual Winches (1)-12K & (1)-8K	
8K Dual Winches	30-ft Deck Only
CHASSIS	
Minimum GVWR (w/o Wheel Lift)	25,500-lb
Minimum GVWR (w/ Wheel Lift)	33,000-lb
Cab to Axle (CA) Range	138-in - 150-in (22-ft Deck) 156-in - 168-in (24-ft Deck) 180-in - 192-in (26-ft Deck) 204-in - 214-in (28-ft Deck) 228-in - 238-in (30-ft Deck)



Visit [jerrdan.com](http://jerrdan.com) for more info on warranty.

FEATURES	STANDARD	OPTIONAL
<b>CONTROLS</b>		
Dual Lighted Side Controls	•	
Wireless Remote (Up to 5 Functions)		•
<b>DECK &amp; SUBFRAME</b>		
Single Sheet 3/16-in Diamond or Smooth Decking	•	
5-in Removable Tubular Steel Rails		•
5-in Polished Aluminum Blade Rails		•
102-in Deck Width	•	
Center Mounted Hydraulic Valve	•	
12 Keyslots	•	
Hydraulic Pressure Gauge	•	
Hose & Wiring Track System	•	
Outboard Tilt Cylinders	•	
Rear Subframe Chain Boxes with Safety Chains	•	
Hi Vis Reflective Tape Rear of Sub Frame		•
Deck Approach Tip Rollers		•
Greaseable Pivot Joints (Cylinders and Pivot Pins)		•
Folding 3 Step Ladder		•
Side Recovery System (SRS) (SRS-10K) Available with Combo Remote (16-in of Frame Clear Space Required)		•
Galvanized Subframe & Wheel Lift		•
<b>LIGHTING &amp; ELECTRICAL</b>		
LED Lighting	•	
LED Work Lights		•
Rear Awareness Indicator Lights (RAIL)		•
<b>ACCESSORIES</b>		
Air Supply Disconnect (End of Subframe Mounted at LH Taillights)		•
SS Quarter Fenders		•
Toolbox (36-in, 48-in or 60-in)		•
Toolbox Trays		•

FEATURES	STANDARD	OPTIONAL
<b>TOWING ACCESSORIES</b>		
Strap and Chain Kit: • 2- 2-in x 96-in Strap w/RTJ Hook • 2- 2-in Ratchet w/12-in Chain • 2- 5/16-in x 10-ft Chain, RTJ Hooks One End and Grab Hook on the Other • 1- 5/16-in V-Chain w/RTJ Hooks Each End and Grab Hooks at Center	•	
8 Point Tie Down Kit		•
Trailer Glad Hands & 7 Way Connector with Mounting Bracket		•
Wheel Lift Grids (Manual L Arms)		•
Camlocks ILO of T-Handle Manual L Arms		•
Reese Receiver ILO of Ball Hitch Mounting Plate (Manual Grids) 2-in or 2.5-in Reese Available		•
Hydraulic Rear Dock Stabilizer (Various Trailer Towing Provisions Available) *Option Available when Wheel Lift is Deleted		•
<b>WINCH &amp; WIRE ROPE</b>		
10,000-lb Worm Gear Winch w/ 7/16-in x 56-ft EIPS Galvanized Wire Rope		•
12,000-lb Worm Gear w/ 7/16-in x 56-ft EIPS Galvanized Wire Rope (Only Available w/ Single Manual Free Spool)		•
Dual 8,000-lb Worm Gear Winches w/ 3/8-in x 56-ft EIPS Galvanized Wire Rope (Only Available on 28-ft & 30-ft)		•
Dual Side Manual Free Spool (10,000-lb Winch Only)		•
Air Controlled Winch Free Spool (10,000-lb Winch Only)		•
<b>HEADBOARD</b>		
Adjustable Headboard Height 45.5-in - 65.5-in Class 6 and Above Chassis		•
Deluxe Headboard Height 36.5-in, 45.5-in, 50.5-in, 57.5-in		•
Stationary Headboard Base Mount , Fits Standard Deck Mounted Headboards to Frame Mounted Stationary (12-in Clear Space Required)		•
Headboard Mounted Chain Racks		•
Headboard Mounted Propane Tank Holder		•
Headboard Mounted Side Grab Handles		•